

## 075 SERIES PRODUCT BRIEF

### Description

A 75mm framed, dedicated double glazed, horizontal sliding window system suitable for residential and low rise commercial applications.

### Types

- XO & XOX configurations
- Continuous jamb, window walls
- Fixed windows

### Features

- Laboratory tested and NATA certified to 300 Pa. water.
- Recessed sashes for improved thermal performance (reduces the exposed surface area of aluminium) and clean sight lines.
- Dual PVC weather baffles (to the sill) and mohair seals combine to achieve excellent weather resistance.
- Sill buffer (to the sill) limits sash travel and ensures safe operation.
- Accommodates 19mm Insulated Glass Units (IGU's) only.
- Fly, security and Crimsafe screens are fitted within the perimeter frame from either the inside or outside (the ability to fit from the interior is a major advantage for multi-level dwellings).
- Compatible with 138 Series and 100mm framing systems using 138-014 with adaptor.

### Hardware

- Height adjustable, double bogey rollers with stainless steel outer carriage, weight rated to 22 kg per roller carriage.
- A die cast, cam-action latch located at the interlock stile for convenient access and a 'positive' locking action.
- Closed cell PVC foam gaskets (to the frame corner joints).

### Limitations

- XO windows are not to exceed 1500mm (h) x 1810mm (w).
- XOX windows are not to exceed 1500mm (h) x 2410mm (w).
- Fixed panels are not to exceed 1.8m<sup>2</sup> in any height/width combination.

N.B. Some dimensions detailed above may be nominal.

Due to continual product development, G.James reserves the right to change, delete or add any information, section profiles, construction details and specifications relating to this product without notice.