

415 SERIES PRODUCT BRIEF

Description

A fixed louvre system suitable for sun screens, creating privacy or other applications where a constant or regulated ventilation is required e.g. plant rooms, substations etc.

Types

- 42mm framed / 39mm (deep) sloped blade.
- 100mm framed / 96.5mm (deep) sloped blade.
- 100mm framed / 96.5mm (deep) stepped blade.
- Plant room louvre units with flanged perimeter frames.
- Sunscreen blades with vertical fins & custom design bracketing.
- Assorted '2 Stage' & '3 Stage' vertical louvre blade systems.
- Sliding louvre shutter system (incorporated within the 445 Series door).
- Louvre screen with hidden mullion using snap support brackets.

Features

- Extruded aluminium blades in various shapes and depth including a coat hanger type blade in a high quality finish superior to roll formed or pressed metal blades.
- Variable blade spacings.

Hardware

- N/A

Limitations

- Maximum recommended blade span – 1500mm without stiffener (100mm blade types).
- Consult your G.James representative if your project specifies a required airflow in litres/sec./m².
- Not recommended where a specified water performance is required.
- To comply with the appropriate design wind load requirement.

N.B. Some dimensions detailed above may be nominal.
Due to continual product development, G.James reserves the right to change, delete or add any information, section profiles, construction details and specifications relating to this product without notice.