

675 SERIES PRODUCT BRIEF

Description

A versatile 150mm x 45mm 'centre pocket' glazed framing system suitable for shopfront, entry door and low rise curtain wall & general framing applications.

Types

- Fixed window & shopfront.
- Pivot, hinged & sliding doors (incorporating 475 Series door rails & stiles).
- Awning & casement windows (incorporating 048 & 265 Series sashes).
- Curtain wall facades (utilising purpose designed drainage transoms).

Features

- Thick walled profiles provide solid support for hinges, door closers etc.
- A unique gasket retention system that firmly secures the glazing gasket into the pocket.
- Internal or external glazing depending on the project & the required location of the removable glazing beads.
- Accommodates 5mm – 10.38mm glass.
- Accessories include sub-framing, a choice of mullion & transom configurations & adaptors (utilising 475 Series).

Hardware

- Extruded PVC glazing gaskets.
- Assorted locks, closers, handles & other associated door furniture as supplied by reputable manufacturers.

Limitations

- Vertical spans for fixed glass not to exceed 3.5 mtrs (guide only)
- Horizontal spans for fixed glass not to exceed 2.4 mtrs (guide only)
- To comply with the appropriate design wind load & human impact requirements and glazing standards.

N.B. Some dimensions detailed above may be nominal.
Due to continual product development, G.James reserves the right to change, delete or add any information, section profiles, construction details and specifications relating to this product without notice.