



SECTION DATA:
 $I_{xx} = 13\,975 \text{ mm}^4$
 $I_{yy} = 13\,975 \text{ mm}^4$
 $\text{Theta} = 0$
 $\text{RadG}_x = 10. \text{ mm}$
 $\text{RadG}_y = 10. \text{ mm}$
 $X_{C_{\text{left}}} = 14.4 \text{ mm}$
 $X_{C_{\text{right}}} = 14.4 \text{ mm}$
 $Y_{C_{\text{top}}} = 14.4 \text{ mm}$
 $Y_{C_{\text{bot}}} = 14.4 \text{ mm}$
 $Z_{xx_{\text{top}}} = 970 \text{ mm}^3$
 $Z_{xx_{\text{bot}}} = 970 \text{ mm}^3$
 $Z_{yy_{\text{left}}} = 970 \text{ mm}^3$
 $Z_{yy_{\text{right}}} = 970 \text{ mm}^3$

0.40 RADIUS ON ALL OUTSIDE CORNERS
UNLESS OTHERWISE SPECIFIED

EXTRUDED FINISH : ARCHITECTURAL

| | | | | | | | | | | | | | |
|----|------|----|----------|---|--|--------------|-------|-------|--|-----------------------|--|------------------------|----------|
| | | | | A | | AREA | 152.7 | SQ MM |  G. James Extrusion Co. A.C.N 010 828 234 1082 KINGSFORD SMITH DRIVE, EAGLE FARM, QUEENSLAND, 4009 PO BOX 1376, EAGLE FARM BC, 4009 PHONE : (07) 3877 2833 FAX : (07) 3877 2890 | CUSTOMER | | G. JAMES EXTRUSION Co. | |
| | | | | | | WEIGHT | 0.414 | KG M | | CUSTOMER PART NAME | | NO. | |
| | | | | | | PERIMETER | 169.6 | MM | | 28.8 x 1.8 ROUND TUBE | | | |
| | | | | | | ANOD PERIM | 90.5 | MM | | SCALE | TOLERANCES IN ACCORDANCE WITH AS 1866-1986 APPLY UNLESS OTHERWISE SPECIFIED | | |
| | | | | | | PAIN PERIM | 100.0 | MM | | 1:1 | | | |
| | | | | | | C CIRCLE DIA | 29. | MM | | DRAWN | CHECK | DATE | DWG. NO. |
| | | | | | | FACTOR | 410. | | | JWC | | 06/04/87 | 950-075 |
| | | | | | | ALLOY | 6063 | | | | | | |
| | | | | | | TEMPER | T6 | | | | | | |
| NO | DATE | DR | REVISION | | | | | | | | | | |